

simply **IPSO®**

On-Premises Laundry

IPH Series Washer-Extractor

On-premises laundries face enough daily challenges, wrestling with complicated, inefficient equipment shouldn't be one of them. IPSO IPH model washer-extractors combine proven designs with user-friendly controls to streamline the laundry process. Our goal is building equipment that's simple to own and even more simple to operate.

Simplifying Ownership

VERSATILE. The PS40 microprocessor offers managers the highest level of control to set spin speeds and water levels, while a simple design ensures employees are quickly trained on its operation. It comes with 10 preprogrammed cycles and room to customize 30 additional cycles. Programming is easily accomplished by uploading from a PC through an infrared connection.

RUGGED RELIABILITY. A heavy-duty steel frame, with a minimum of welds, provides one of the most stable bases on the market. That translates into years of worry-free operation.

VALUE. The high extract speeds of IPH washer-extractors can produce results similar to more expensive softmount units. Added value comes in the reduced utility consumption and time savings as drying times are decreased.

TIME SAVINGS. The IPH's automatic supply injection system eliminates the need for staff to manually add chemicals. This saves valuable minutes during a shift and allows employees to concentrate on other laundry tasks.

PEACE OF MIND. A 3-year parts warranty (5-years on major components) is standard.

WASHABILITY. While the IPH is designed to increase productivity and efficiency, managers don't have to sacrifice quality. IPSO washer-extractors deliver superior finished results.



THE BOTTOM LINE. We believe the efficiency in design and operation of our washer-extractors combined with the features of our intuitive controls will have the ultimate impact on your laundry's productivity and bottom line. Put simply, IPSO gets results.

IP040 - 40 lb Washer-Extractor
IP060 - 60 lb Washer-Extractor
IP080 - 80 lb Washer-Extractor
IP100 - 100 lb Washer-Extractor
IP125 - 125 lb Washer-Extractor
IP140 - 140 lb Washer-Extractor
IP175 - 175 lb Washer-Extractor



IPH Series Washer-Extractor Specifications

	IP040	IP060	IP080	IP100	IP125	IP140	IP175					
Capacity - lb (kg)	40 (18)	60 (27)	80 (36)	100 (45)	125 (57)	140 (64)	175 (79)					
Height - in (mm)	57" (1448)	62 5/8" (1590)	70" (1778)	70" (1778)	77 1/8" (1958)	77 1/8" (1958)	77 1/8" (1958)					
Width - in (mm)	32" (813)	34 1/2" (876)	42 1/2" (1080)*	42 1/2" (1080)*	50 5/16" (1278)*	50 5/16" (1278)*	50 5/16" (1278)*					
Depth - in (mm)	45 5/8" (1158)	47 13/16" (1214)	51 7/16" (1305)	56 7/16" (1432)	56 1/8" (1425)	59 1/8" (1501)	64 1/8" (1628)					
Door Opening - in (mm)	15" (381)	17" (432)	20" (508)	20" (508)	24 1/2" (622)	24 1/2" (622)	28 1/2" (724)					
Net Weight - lb (kg)	1690 (766)	1795 (814)	1926 (874)	2167 (983)	2749 (1247)	3027 (1373)	3277 (1486)					
Crated Weight - lb (kg)	1770 (803)	1895 (859)	2026 (919)	2267 (1028)	2849 (1292)	3127 (1418)	3327 (1509)					
Cylinder Dimensions												
Diameter - in (mm)	27" (686)	31" (787)	37" (940)	37" (940)	43" (1092)	43" (1092)	43" (1092)					
Depth - in (mm)	19" (483)	22" (559)	21" (533)	26" (660)	24" (610)	27" (686)	32" (813)					
Volume - cu.ft. (liters)	6.3 (178.3)	9.6 (271.7)	13.1 (370.7)	16.2 (458.5)	20.1 (569.2)	22.7 (642.4)	26.8 (759.9)					
Cylinder Speed												
Wash - RPM	46	43	39	39	36	36	36					
Extract - RPM	885	826	756	756	701	640	640					
G-Force - RPM	300	300	300	300	300	250	250					
Drain Size - in (mm)	3" (76)	3" (76)	3" (76)	3" (76)	3" (76)	3" (76)	3" (76)					
Water Inlet - (std/opt)	2/3	2/3	2/3	2/3	2/3	2/3	2/3					
Voltage/Hz/Phase												
Circuit Breaker - FLA												
(Q)	208-240/50/60/3ph	15-7.5	208-240/50/60/3ph	20-11.7	208-240/50/60/3ph	30-15.5	208-240/50/60/3ph	30-21.1	208-240/50/60/3ph	30-21.1	N/A	
(N)	380-480/50/60/3ph	15-3.9	380-480/50/60/3ph	15-6.2	380-480/50/60/3ph	20-8.1	380-480/50/60/3ph	20-8.1	380-480/50/60/3ph	20-11.1	380-480/50/60/3ph	20-13.3
Agency Approvals	CE, ETL _{US} , ETL _C	CE, ETL _{US} , ETL _C	CE, ETL _{US} , ETL _C	CE, ETL _{US} , ETL _C	CE, ETL _{US} , ETL _C	CE, ETL _{US} , ETL _C	CE, ETL _{US} , ETL _C	CE, ETL _{US} , ETL _C	CE, ETL _{US} , ETL _C	CE, ETL _{US} , ETL _C		

* Add 6" to width for External Soap Dispenser (sidemount) on IP080 and larger models.

For the most accurate information the installation guide should be used for all design and construction purposes. Due to continuous improvements, design and specifications subject to change without notice. The quality management systems at all Alliance Laundry Systems manufacturing facilities are registered as ISO 9001:2000 compliant. Features and certifications may vary by model.

©Copyright 2007 Alliance Laundry Systems LLC

Control Options



PS40 Microprocessor

[Click here for pricing](#)

For more info please contact us:

phone: 1-877-257-4783

1-909-659-1785

fax: 1-909-872-1121

e-mail: sales@agapelaundrysystems.com

or just click here

